

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁵ :

A61M 5/155

A1

(11) International Publication Number:

WO 93/23096

(43) International Publication Date: 25 November 1993 (25.11.93)

(21) International Application Number: PCT/IE93/00024

(22) International Filing Date: 29 April 1993 (29.04.93)

(30) Priority data:
921613

20 May 1992 (20.05.92) IE

(71) Applicant: ELAN MEDICAL TECHNOLOGIES LIMITED [IE/IE]; Monksland Industrial Estate, Athlone, County Westmeath (IE).

(72) Inventor: GROSS, Joseph ; 41 Orwell Park, Rathgar, Dublin 6 (IE).


(74) Agent: ANNE RYAN & CO.; 60 Northumberland Road, Ballsbridge, Dublin 4 (IE).

(81) Designated States: AU, CA, JP, KR, NZ, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).

Published

With international search report.

(54) Title: LIQUID MATERIAL DISPENSER



(57) Abstract

A liquid material dispenser for dispensing medicaments includes a housing (2) formed with a reservoir (4) for the liquid to be dispensed, an outlet (6) through which the liquid is to be dispensed, and a connecting passageway (8) between the reservoir (4) and the outlet (6). A diaphragm (12) is located in a cavity (10) in the passageway (8) such that one side of the diaphragm (12) defines a pumping chamber (10a), and the other side defines a control chamber (10b). An electrolytic cell (14) generates a gas which is fed to the control chamber (10b) according to the quantity of electrical current passed through the electrolyte (14c), for driving the diaphragm (12) through forward strokes to pump liquid to the outlet (6); and a slow-acting vent (20) vents the gas from the control chamber (10b) to the atmosphere at a rate lower than that of generation of gas by the electrolytic cell (14), for driving the diaphragm (12) through return strokes to refill the pumping chamber (10a).

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	FR	France	MR	Mauritania
AU	Australia	GA	Gabon	MW	Malawi
BB	Barbados	GB	United Kingdom	NL	Netherlands
BE	Belgium	GN	Guinea	NO	Norway
BF	Burkina Faso	GR	Greece	NZ	New Zealand
BG	Bulgaria	HU	Hungary	PL	Poland
BJ	Benin	IE	Ireland	PT	Portugal
BR	Brazil	IT	Italy	RO	Romania
CA	Canada	JP	Japan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SK	Slovak Republic
CI	Côte d'Ivoire	LI	Liechtenstein	SN	Senegal
CM	Cameroon	LK	Sri Lanka	SU	Soviet Union
CS	Czechoslovakia	LJ	Luxembourg	TD	Chad
CZ	Czech Republic	MC	Monaco	TG	Togo
DE	Germany	MG	Madagascar	UA	Ukraine
DK	Denmark	ML	Mali	US	United States of America
ES	Spain	MN	Mongolia	VN	Viet Nam
FI	Finland				

Description

Liquid Material Dispenser

Technical Field

5 The present invention relates to liquid material dispensers, and particularly to dispensers for dispensing medicaments at small, precisely-controlled rates. The invention is especially useful in a dispenser including an electrolytic cell generating a gas in accordance with the rate the liquid is to be dispensed, such as described in prior U.S. Patent Nos. 5,062,834 and 5,090,963, and it is therefore described
10 below particularly with respect to such a dispenser.

Background Art

 There are many applications, such as drug delivery systems, requiring the dispensing or delivering of a liquid at a predetermined, precisely-controlled rate. Electrolytic pumps, such as described in the
15 above U.S. Patents, have been developed for this purpose. These pumps, however, generally include relatively large pumping chambers, and therefore their pumping rates may be significantly influenced by pressure and temperature changes particularly when the dispenser is used over long periods of time and/or under varying ambient
20 conditions.

 It would therefore be desirable to provide a liquid material dispenser or pump of a construction which may include a pumping chamber of relatively small volume so that the rate of delivery of the liquid is less sensitive to pressure and temperature changes.

25 Disclosure of Invention

 According to the present invention, there is provided a liquid material dispenser, comprising:

a housing including a reservoir for liquid to be dispensed, an outlet through which the liquid is dispensed, and a connecting passageway between said reservoir and said outlet;

5 a reciprocable pumping member in the passageway, such that one side of the pumping member defines a pumping chamber with the passageway, and the other side defines a pressure-control chamber, said pumping member being cyclically displaceable through forward and return strokes for pumping liquid from said reservoir to said outlet;

10 valve means in said passageway effective, during one of said strokes, to cause the pumping member to draw liquid from said reservoir into said pumping chamber, and during the other of said strokes, to cause the pumping member to pump liquid from said pumping chamber through said outlet;

15 feeding means for feeding a gas at a preselected time and rate to said pressure-control chamber to drive the pumping member through one of said strokes;

20 and a slow-acting vent for venting the gas from said pressure-control chamber to the atmosphere continuously at a rate lower than said gas feeding rate, to drive the pumping member through the other of said strokes.

25 According to a further feature in the preferred embodiment of the invention described below, the feeding means comprises an electrolytic cell including electrodes and an electrolyte which generates a gas according to the quantity of the electrical current passed through the electrolyte.

According to a still further feature, the slow-acting vent comprises a gas-permeable porous member. The latter member may be of sintered metal or sintered plastics material.

As will be described more particularly below, such a dispenser may be operated by closing an electrical circuit to the electrolytic cell to cause gas to be generated at a predetermined rate and during a predetermined time period, e.g., one minute, and then interrupting the current supplied to the electrolytic cell for a longer interval, e.g., four minutes. Thus, during the one-minute interval, gas will be generated to drive the pumping member (e.g., a diaphragm) through a forward stroke to pump liquid from the pumping chamber through the outlet; and during the subsequent four-minute interval when no gas is generated, the slow-acting vent vents the gas from the pressure-control chamber to the atmosphere to thereby drive the pumping member through the return stroke to draw liquid from the reservoir to the pumping chamber.

In such a construction, the pumping chamber may be of a relatively small volume so that the dispenser is much less sensitive to temperature and pressure fluctuations, and therefore can more precisely control the delivery of the liquid. This is particularly important when very low delivery rates are involved such as in the administration of medicaments to a patient.

Further features and advantages of the invention will be apparent from the description below.

Brief Description of Drawing

The accompanying figure is a front elevation in section of a preferred embodiment of a liquid material dispenser according to the invention.

The invention is herein described, by way of example only, with reference to the accompanying single drawing figure.

Best Mode for Carrying Out the Invention

The illustrated preferred embodiment is a liquid material dispenser for delivering drugs at a slow, controlled and precise rate, to a patient. It includes an electrolytic cell, such as described in prior U.S. Patent Nos. 5,062,834 and 5,090,963 referred to above, for controlling the rate and time of delivery of the drug to the patient.

The illustrated liquid material dispenser includes a housing, generally designated 2, having a reservoir 4 for the liquid to be dispensed, an outlet 6 through which the liquid is dispensed, and a connecting passageway 8 between the reservoir and the outlet. Passageway 8 includes an enlarged cavity 10 occupied by a diaphragm 12.

Diaphragm 12 serves as a reciprocable pumping member and is cyclically displaceable through forward and return strokes for pumping liquid from reservoir 4 through the outlet 6. The cyclical reciprocation of diaphragm 12 is effected by an electrolytic cell, generally designated 14, within a compartment 16 in housing 2 and communicating with cavity 10 at one side of the diaphragm *via* a bore 18. It will thus be seen that the diaphragm defines a pumping chamber 10a on one side for pumping liquid from the reservoir 4 through the outlet 6, and a pressure-control chamber 10b on the opposite side, communicating *via* bore 18 with electrolytic cell 14 in compartment 16.

Two one-way umbrella valves V_1 , V_2 are in the connecting passageway 8 between reservoir 4 and outlet 6. Valve V_1 is proximal to the outlet 6, i.e., between it and pumping chamber 10a, and is oriented such that during the forward strokes of diaphragm 12, the diaphragm pumps liquid from the pumping chamber 10a through the outlet 6 *via* section 8a of the connecting passageway 8. Valve V_2 is located proximal to the reservoir 4, i.e., between it and pumping chamber 10a, and is oriented such that during the return strokes of the diaphragm 12, it permits the diaphragm to draw liquid from the

reservoir 4 into the pumping chamber 10_a *via* section 8_b of the connecting passageway 8.

As will be described more particularly below, the electrolytic cell 14 in compartment 16 is electrically controlled to generate a gas at a preselected time and at a preselected rate and to feed the gas to the pressure-control chamber 10_b acting on diaphragm 12, to drive the diaphragm through its forward strokes for pumping liquid from the pumping chamber 10_a to the outlet 6 *via* valve V₁. The illustrated dispenser further includes a slow-acting vent 20 for venting the gas from the pressure-control chamber 10_b to the atmosphere continuously, and at a rate lower than the gas feeding rate, to drive the diaphragm through the return strokes, and thereby to draw liquid from reservoir 4 into the pumping chamber 10_a.

The slow-acting vent 20 is in the form of a gas-permeable porous cap. It may be of sintered metal particles, such as of steel, copper, aluminium, titanium, etc.; alternatively, it may be of sintered plastics particles, such as of polypropylene or polytetrafluorethylene, such as "Teflon" (Trade Mark).

The gas-permeable cap 20 is received within an apertured seat, e.g., of plastics material, fixed to housing 2 and is retained in the seat by any suitable means, such as by a plastics clip 24. An O-ring 26 is interposed between cap 20 and the outer face of seat 22. The inner face of seat 22 carries a hydrophobic membrane 28 which is permeable to gas but not to liquid, to thereby prevent electrolyte 14_c from clogging the cap.

The electrolytic cell 14, located within compartment 16 communicating with the pressure-control chamber 10_b on one side of diaphragm 12, may be of any known construction, such as described in prior U.S. Patent N s. 5,062,834 and 5,090,963. Basically, it includes a pair of electrodes 14_a, 14_b, and electrolyte 14_c which generates a gas according to the quantity of electrical current passed through the electrolyte. The two electrodes 14_a, 14_b are connected to terminals 30,

32 for connection to an external electrical control circuit 34 (indicated schematically). As known in such electrolytic-type pumps, the electrical control circuit 34 includes electrical switching means 35 for controlling the time at which electrical current is applied to the electrolytic cell 14, and also current-control means 36 for controlling the magnitude of the applied electrical current, and thereby the rate of generation of the gas by the electrolytic cell.

Housing 2, reservoir 4, and/or diaphragm 12, may be of any suitable configuration, e.g., circular or rectangular in cross-section.

For ease in assembly and disassembly of the illustrated dispenser, housing 2 is made of a plurality of sections, namely: a first section 2a; a second section 2b clamping diaphragm 12 between it and section 2a; a third section 2c defining, with section 2a, the pressure-control chamber 10b on one side of diaphragm 12 and including the electrolytic cell compartment 16; a fourth section 2d secured at one end to housing sections 2a, 2b and 2c; and a fifth section 2e secured to the opposite end of housing section 2d. A rolling diaphragm 38 is clamped between the two sections 2d, 2e; and an air vent opening 40 is formed in housing section 2e.

It will thus be seen that the reservoir 4 is defined by housing section 2d and the rolling diaphragm 38. Housing section 2d carries an injection plug 42 for filling the reservoir 4 by injection via a syringe needle, as is well known. Diaphragm 38 and vent opening 40 permit reservoir 4 to expand and contract according to the quantity of the liquid material contained in the reservoir.

The base of one-way umbrella valve V₁ is secured in an opening formed in housing section 2a; and the base of one-way umbrella valve V₂ is secured in an opening formed in a rigid plastics member 44 between housing sections 2b and 2a.

The illustrated dispenser operates in the following manner:

Reservoir 4 is filled by a syringe piercing the injection plug 42 until the injected liquid drug begins to exit from the outlet 6. When this occurs, not only is the reservoir 4 completely filled with the liquid drug, but also the connecting passageway 8 and the cavity 10 are filled with the drug up to the outlet 6.

The time and rate of delivery of the drug from reservoir 4 to the outlet 6 are controlled by the electrical control circuit 34 for energizing the electrolytic cell 14 *via* its electrodes 14a, 14b and their electrical terminals 30, 32, respectively. As one example, the electrical control circuit 34 may be such so as to energize the two electrodes 14a, 14b at periods of one minute followed by intervals of four minutes. During the one-minute interval when the electrodes 14a, 14b are energized, the electrolyte 14c generates a gas which is fed *via* bore 18 to the pressure-control chamber 10b at one side of diaphragm 12. This gas displaces the diaphragm, as shown in broken lines at 12' in the drawing, thereby stressing the diaphragm to contract the pumping chamber 10a. This contraction of the pumping chamber applies a pressure *via* section 8b of the connecting passageway 8 to close valve V₂, and also applies a pressure *via* section 8a of the connecting passageway to open valve V₁. Accordingly, liquid from pumping chamber 10a is pumped *via* valve V₁ through the outlet 6 for the one-minute period during which the electrolytic cell 14 is energized, and at a rate corresponding to the magnitude of electrical current passed through the electrolyte.

The pressure-control chamber 10b is continuously vented to the atmosphere *via* the gas-permeable porous cap 20. Since the rate of venting of the gas is less than the rate of generation of the gas by the electrolytic cell 14, this venting of the gas does not substantially influence the dispenser during the pumping stroke. However, as soon as the pumping stroke is completed by the termination of the electrical current applied to the electrolytic cell 14 (e.g., after one minute), the venting of the gas *via* cap 20 to the atmosphere slowly reduces the

pressure in chamber 10_b so that the stressed diaphragm 12 tends to move back to its initial condition (shown in full lines in the drawing), thereby expanding the pumping chamber 10_a. This expansion of the pumping chamber lowers the pressure in passageway section 8_a to close valve V₁; it also lowers the pressure in passageway section 8_b to open valve V₂ and to draw liquid from reservoir 4 into the pumping chamber 10_a.

Thus, at the end of the interval (e.g., four minutes) following the termination of the electrical current applied to the electrolytic cell 14, diaphragm 12 will have been returned to its home position (shown in full lines in the drawing), and pumping chamber 10_a will have been refilled with liquid from reservoir 4. When electrical current is again applied to the electrolytic cell 14 to generate additional gas, the diaphragm 12 will again be driven through a forward pumping stroke for pumping the liquid within pumping chamber 10_a via valve V₁ through the outlet 6.

It will be appreciated that the illustrated dispenser does not hold large volumes of gases over extended periods, and therefore is not significantly sensitive to temperature and pressure fluctuations. The illustrated dispenser may therefore be used for dispensing liquids at precisely-controlled rates and over long periods of time between refillings.

While the invention has been described with respect to one preferred embodiment, it will be appreciated that many other variations, modifications and applications of the invention may be made.

CLAIMS:

1. A liquid material dispenser, comprising:

5 a housing including a reservoir for liquid to be dispensed, an outlet through which the liquid is dispensed, and a connecting passageway between said reservoir and said outlet;

10 a reciprocable pumping member in the passageway, such that one side of the pumping member defines a pumping chamber with the passageway, and the other side defines a pressure-control chamber, said pumping member being cyclically displaceable through forward and return strokes for pumping liquid from said reservoir to said outlet;

15 valve means in said passageway effective, during one of said strokes, to cause the pumping member to draw liquid from said reservoir into said pumping chamber, and during the other of said strokes, to cause the pumping member to pump liquid from said pumping chamber through said outlet;

feeding means for feeding a gas at a preselected time and rate to said pressure-control chamber to drive the pumping member through one of said strokes;

20 and a slow-acting vent for venting the gas from said pressure-control chamber to the atmosphere continuously at a rate lower than said gas feeding rate, to drive the pumping member through the other of said strokes.

25 2. A dispenser according to Claim 1, wherein said feeding means comprises an electrolytic cell including electrodes and an electrolyte which generates a gas according to the quantity of electrical current passed through said electrolyte.

3. A dispenser according to Claim 1 or 2, wherein said slow-acting vent comprises a gas-permeable porous member.

4. A dispenser according to Claim 3, wherein said gas-permeable porous member is of sintered metal.

5 5. A dispenser according to Claim 3, wherein said gas-permeable porous member is of sintered plastics material.

10 6. A dispenser according to any preceding claim when dependent on Claim 3, wherein a hydrophobic membrane is provided between said pressure-control chamber and said gas-permeable porous member.

15 7. A dispenser according to Claim 6, wherein said gas-permeable porous member is in the form of a cap mounted on an apertured seat fixed to the housing, which an O-ring disposed between the cap and one side of the seat, said hydrophobic membrane being disposed between the other side of the seat and the pressure-control chamber.

8. A dispenser according to any preceding claim, wherein said pumping member is a diaphragm.

20 9. A dispenser according to Claim 8, wherein said feeding means includes an electrolytic cell communicating with said pressure-control chamber, said electrolytic cell including electrodes and an electrolyte which generates a gas according to the quantity of electrical current passed through said electrolyte.

25 10. A dispenser according to Claim 9, wherein said housing includes at least three sections, said diaphragm being clamped between first and second housing sections, said pressure-control chamber being defined by said first section and a third section, said first section being formed with a passageway leading to said diaphragm.

11. A dispenser according to Claim 10, wherein said housing includes a fourth section and a fifth section, said fourth section being secured to said second section, and said fifth section being secured to said fourth section with a second diaphragm therebetween, said
5 reservoir being defined by said fourth section and said second diaphragm, said fifth section including a venting opening and defining a venting chamber with said second diaphragm.

12. A dispenser according to any preceding claim, wherein said valve means comprises:

10 a first one-way valve in said passageway proximal to said outlet and oriented such that during one of said strokes the pumping member pumps liquid from said pumping chamber through said outlet; and

15 a second one-way valve in said passageway proximal to said reservoir and oriented such that during the other of said strokes the pumping member draws liquid from said reservoir to said pumping chamber.

13. A dispenser according to Claim 12, wherein said first and second valves are umbrella valves cooperable with valve openings
20 formed in said housing.

14. A liquid material dispenser, comprising:

a housing including a reservoir for liquid to be dispensed, an outlet through which the liquid is to be dispensed, and a connecting passageway between said reservoir and said outlet;

25 a diaphragm in the passageway such that one side of the diaphragm defines a pumping chamber, and the other side defines a pressure-control chamber;

an electrolytic cell communicating with said control chamber and including electrodes and an electrolyte which generates a gas according to the quantity of electrical current passed through said electrolyte, for driving said diaphragm through forward strokes;

5 a slow-acting vent for venting the gas from said pressure-control chamber to the atmosphere at a rate lower than that of generation of gas by said electrolytic cell, for driving the diaphragm through return strokes;

10 and valve means in said passageway causing the diaphragm to pump liquid from said pumping chamber through said outlet during said forward strokes, and to draw liquid from said reservoir into said pumping chamber during said return strokes.

15 15. A dispenser according to Claim 14, wherein said slow-acting vent comprises a gas-permeable porous member.

16. A dispenser according to Claim 15, wherein said gas-permeable porous member is of sintered metal.


17. A dispenser according to Claim 15, wherein said gas-permeable porous member is of sintered plastics material.

20 18. A dispenser according to any one of Claims 15-17, wherein a hydrophobic membrane is provided between said pressure-control chamber and said gas-permeable porous member.

25 19. A dispenser according to any one of Claims 15-18, wherein said gas-permeable porous member is in the form of a cap mounted on an apertured seat fixed to the housing, with an O-ring disposed between the cap and one side of the seat, said hydrophobic membrane being disposed between the other side of the seat and the pressure-control chamber.

20. A dispenser according to any one of Claims 14-19,
wherein said housing includes at least three sections, said diaphragm
being clamped between first and second housing sections, said pressure-
control chamber being defined by said first section and a third section,
5 and said first section being formed with a passageway leading to said
diaphragm.

1/1



INTERNATIONAL SEARCH REPORT

International Application No

PCT/IE 93/00024

I. CLASSIFICATION OF SUBJECT MATTER (If several classification symbols apply, indicate all) * According to International Patent Classification (IPC) or to both National Classification and IPC IPC ⁵ : A 61 M 5/155						
II. FIELDS SEARCHED <div style="text-align: center; border-top: 1px solid black; border-bottom: 1px solid black; margin: 5px 0;">Minimum Documentation Searched †</div> <table style="width: 100%; border-collapse: collapse;"> <tr> <th style="width: 30%; border-bottom: 1px solid black;">Classification System</th> <th style="width: 70%; border-bottom: 1px solid black;">Classification Symbols</th> </tr> <tr> <td style="border-right: 1px solid black; padding: 5px;">IPC⁵</td> <td style="padding: 5px;">A 61 M</td> </tr> </table> <div style="border-top: 1px solid black; padding-top: 5px; margin-top: 10px;"> Documentation Searched other than Minimum Documentation to the extent that such Documents are included in the Fields Searched * </div>			Classification System	Classification Symbols	IPC ⁵	A 61 M
Classification System	Classification Symbols					
IPC ⁵	A 61 M					
III. DOCUMENTS CONSIDERED TO BE RELEVANT ‡						
Category *	Citation of Document, † with indication, where appropriate, of the relevant passages ‡	Relevant to Claim No. ‡				
A	US, A, 4 687 423 (H.MAGET et al.) 18 August 1987 (18.08.87), the whole document. --	1, 2, 14				
A	US, A, 5 090 963 (J.GROSS et al.) 25 February 1992 (25.02.92), fig. 1,2; column 3, lines 13-68; column 5, line 50 - column 6, line 8; (cited in the application). --	1, 2, 14				
A	US, A, 3 115 280 (S.P.BATTISTA) 24 December 1963 (24.12.63), the whole document; especially column 2, lines 58-64. --	1, 2, 14				
A	US, A, 4 944 659 (J.M. LABB et al.)	1				
<table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 50%; vertical-align: top; padding: 5px;"> * Special categories of cited documents: † "A" document defining the general state of the art which is not considered to be of particular relevance "E" earlier document but published on or after the international filing date "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) "O" document referring to an oral disclosure, use, exhibition or other means "P" document published prior to the international filing date but later than the priority date claimed </td> <td style="width: 50%; vertical-align: top; padding: 5px;"> "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art "A" document member of the same patent family </td> </tr> </table>			* Special categories of cited documents: † "A" document defining the general state of the art which is not considered to be of particular relevance "E" earlier document but published on or after the international filing date "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) "O" document referring to an oral disclosure, use, exhibition or other means "P" document published prior to the international filing date but later than the priority date claimed	"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art "A" document member of the same patent family		
* Special categories of cited documents: † "A" document defining the general state of the art which is not considered to be of particular relevance "E" earlier document but published on or after the international filing date "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) "O" document referring to an oral disclosure, use, exhibition or other means "P" document published prior to the international filing date but later than the priority date claimed	"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art "A" document member of the same patent family					
IV. CERTIFICATION						
Date of the Actual Completion of the International Search <div style="text-align: center; font-size: 1.2em;">22 July 1993</div>		Date of Mailing of this International Search Report <div style="text-align: center; font-size: 1.2em;">13. 08. 93</div>				
International Searching Authority <div style="text-align: center; font-weight: bold;">EUROPEAN PATENT OFFICE</div>		Signature of Authorized Officer				

III. DOCUMENTS CONSIDERED TO BE RELEVANT (CONTINUED FROM THE SECOND SHEET)		
Category *	Citation of Document, " with indication, where appropriate, of the relevant passages	Relevant to Claim No.
	<p>31 July 1990 (31.07.90), the whole document.</p> <p>-----</p>	

ANHANG

zum internationalen Recherchen-
bericht über die internationale
Patentansmeldung Nr.

ANNEX

to the International Search
Report to the International Patent
Application No.

ANNEXE

au rapport de recherche inter-
national relatif à la demande de brevet
international n°

PCT/IE 93/00024 SAE 72997

In diesen Anhang sind die Mitglieder
der Patentfamilien der im obenge-
nannten internationalen Recherchenbericht
angeführten Patentdokumente angegeben.
Diese Angaben dienen nur zur Unter-
richtung und erfolgen ohne Gewähr.

This Annex lists the patent family
members relating to the patent documents
cited in the above-mentioned inter-
national search report. The Office is
in no way liable for these particulars
which are given merely for the purpose
of information.

La présente annexe indique les
membres de la famille de brevets
relatifs aux documents de brevets cités
dans le rapport de recherche inter-
national visé ci-dessus. Les renseigne-
ments fournis sont donnés à titre indica-
tif et n'engagent pas la responsabilité
de l'Office.

Im Recherchenbericht angeführtes Patentdokument Patent document cited in search report Document de brevet cité dans le rapport de recherche		Datum der Veröffentlichung Publication date Date de publication	Mitglied(er) der Patentfamilie Patent family member(s) Membre(s) de la famille de brevets	Datum der Veröffentlichung Publication date Date de publication
US A	4687423	18-08-87	DE C0 3672917 EP A1 209677 EP B1 209677 JP A2 61280869	30-08-90 28-01-87 25-07-90 11-12-86
US A	5090963	25-02-92	EP A2 481601 EP A3 481601	22-04-92 03-06-92
US A	3115280		keine - none - rien	
US A	4944659	31-07-90	AU A1 12264/88 AU B2 600098 CA A1 1303929 DK A 5373/88 DK A0 5373/88 EP A1 325618 FI A 884403 FI A0 884403 GB A0 8701731 JP T2 1502045 NO A 884257 NO A0 884257 NO B 167256 NO C 167256 WO A1 8805314	10-08-88 02-08-90 23-06-92 27-09-88 27-09-88 02-08-89 26-09-88 26-09-88 04-03-87 13-07-89 26-09-88 26-09-88 15-07-91 23-10-91 28-07-88